

Copyright c 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio/i ed i segni distintivi della società sono di proprietà esclusiva della satessa.



555T SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel frame, closed firebox with adjustable legs
Firebox: in Aluker® (not available for 510-555 series)
Hood: in steel; on 510-555 adjustable cast iron flue connector
Fire pit: in cast iron
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750°C. Rise n'fall door, hinged opening for cleaning.
Only hinged door on models 510A-555E A-555T A
Door profile: series 610-700-801-810-2010-510-555 in enamelled steel. Series 600-650-655-750 in enamelled steel or stainless steel optional.
Door handle: in enamelled steel, detachable, in nickled finished alloy and silicon covered handle depending on model
Primary air: manual, fixed on 600HT
Secondary air: fixed, manual on 760HT
Flue outlet: top; top or rear on models 510-555
Flue damper: manual; optional on models 510-555
Ash pan: removable
Fuel: wood
Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System®

TECHNICAL DATA

Room heating capacity (min-max)	m ³	135 - 230
Nominal thermal efficiency	%	81
Rated heat output	kW	8
Consumption at rated heat output	Kg/h	2,3
Maximum heat output	kW	10
Maximum consumption	Kg/h	3,5
Flue outlet	Ø cm	18
Flue up to 4,5 mt	Ø cm	22
Flue over 4,5 mt	Ø cm	18
Fresh air intake (recomm. min sect.)	cm ²	150
Weight	Kg	185

ON REQUEST

- Single Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Log retainer
- Manual flue dumper kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

C UNO. - C DUE. - OXFORD. - LEEDS

TECHNICAL DRAWING

