

Copyright c 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio/i ed i segni distintivi della società sono di proprietà esclusiva della satessa.



# 510A

## GENERAL TECHNICAL CHARACTERISTICS

**Structure:** enamelled steel frame, closed firebox with adjustable legs  
**Firebox:** in Aluker® (not available for 510-555 series)  
**Hood:** in steel; on 510-555 adjustable cast iron flue connector  
**Fire pit:** in cast iron  
**Opening:** door in enamelled steel with self-cleaning ceramic glass resistant up to 750°C. Rise n'fall door, hinged opening for cleaning. Only hinged door on models 510A-555E A-555T A  
**Door profile:** series 610-700-801-810-2010-510-555 in enamelled steel. Series 600-650-655-750 in enamelled steel or stainless steel optional.  
**Door handle:** in enamelled steel, detachable, in nickled finished alloy and silicon covered handle depending on model  
**Primary air:** manual, fixed on 600HT  
**Secondary air:** fixed, manual on 760HT  
**Flue outlet:** top; top or rear on models 510-555  
**Flue damper:** manual; optional on models 510-555  
**Ash pan:** removable  
**Fuel:** wood  
**Heating:** natural convection, radiant and forced ventilation kit optional through Multifuoco System®

## TECHNICAL DATA

Room heating capacity (min-max)	m <sup>3</sup>	135 - 230
Nominal thermal efficiency	%	82
Rated heat output	kW	8
Consumption at rated heat output	Kg/h	2,3
Maximum heat output	kW	9
Maximum consumption	Kg/h	3,1
Flue outlet	Ø cm	18
Flue up to 4,5 mt	Ø cm	22
Flue over 4,5 mt	Ø cm	18
Fresh air intake (recomm. min sect.)	cm <sup>2</sup>	150
Weight	Kg	144

## ON REQUEST

- Single Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Log retainer
- Manual flue dumper kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

## Compatible Cover

SIENA - PADOVA - RODI - VELLETRI - CLES