

Copyright c 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio/i ed i segni distintivi della società sono di proprietà esclusiva della satessa.



MA 260 B SL

GENERAL TECHNICAL CHARACTERISTICS

- Structure:** enamelled steel, closed firebox
Firebox: in Aluker®
Fire pit: in cast iron
Hood: in steel
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°.
Rise n fall door, hinged opening for cleaning
Door profile: in enamelled steel
Door handle: in enamelled steel
Primary air: adjustable manually
Secondary air: fixed
Flue outlet: top
Flue damper: manual
Ash pan: removable
Fuel: wood
Heating: radiant and natural convection

TECHNICAL DATA

Room heating capacity (min-max)	m ³	225-390
Nominal thermal efficiency	%	75
Rated heat output	kW	13,5
Consumption at rated heat output	Kg/h	4,2
Maximum heat output	kW	14,5
Maximum consumption	Kg/h	4,8
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. min sect.)	cm ²	200
Weight	Kg	180

ON REQUEST

- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

ESSEN - AMBURGO - LUBECCA - BREMA - FRIBURGO - LIPSIA - VIENNA - COLONIA - DRESDA - ACADEMY - CLASS - EASY - VISION - NOVARA - TOKIO - OLIVETO - ATENE - ISTRIA - MERANO - VENEZIA - PAVIA - VALENCIA - OVIEDO - LIVIGNO

TECHNICAL DRAWING

