

Copyright c 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio/i ed i segni distintivi della società sono di proprietà esclusiva della satessa.



MA 284 SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox

Firebox: in Aluker®

Fire pit: in cast iron

Hood: in steel

Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 °C.
Rise n fall door, hinged opening for cleaning

Door profile: in enamelled steel

Door handle: in enamelled steel

Primary air: adjustable manually

Secondary air: fixed

Flue outlet: top

Flue damper: manual

Ash pan: removable

Fuel: wood

Heating: radiant and natural convection

TECHNICAL DATA

Room heating capacity (min-max)	m ³	210 -360
Nominal thermal efficiency	%	73,5
Rated heat output	kW	12,5
Consumption at rated heat output	Kg/h	4
Maximum heat output	kW	13,5
Maximum consumption	Kg/h	4,6
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. min sect.)	cm ²	300
Weight	Kg	190

ON REQUEST

- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

TECHNICAL DRAWING

