



MC 70/51

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox

Firebox: in Aluker®

Fire pit: in Aluker®

Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Hinged opening

Door profile: in enamelled steel

Door handle: hide away and detachable

Primary air: adjustable manually

Secondary air: adjustable manually

Tertiary air: fixed and preheated

Flue outlet: top.

Fuel: wood

Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System®

TECHNICAL DATA

Room heating capacity (min-max)	m ³	185 - 315
Nominal thermal efficiency	%	79
Rated heat output	kW	11
Consumption at rated heat output	Kg/h	3
Maximum heat output	kW	12
Maximum consumption	Kg/h	3,9
Flue outlet	Ø cm	18
Flue up to 4,5 mt	Ø cm	22
Flue over 4,5 mt	Ø cm	18
Fresh air intake (recomm. min sect.)	cm ²	200
Weight	Kg	140

ON REQUEST

- Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

ESSEN - AMBURGO - LUBECCA - BREMA - FRIBURGO - LIPSIA - VIENNA - COLONIA - DRESDA - ACADEMY - CLASS - EASY - VISION - NOVARA - TOKIO - OLIVETO - ATENE - ISTRIA - MERANO - VENEZIA - PAVIA - VALENCIA - OVIEDO - ARGO - BARGA - VICENZA - LIVIGNO - VIAREGGIO - VIPITENO - PRESTON

TECHNICAL DRAWING

