



## MC 120/48



### GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox  
 Firebox: In Aluke®  
 Fire pit: In Aluke®  
 Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 °C. Hinged opening  
 Door profile: In enamelled steel  
 Door handle: hide away and detachable  
 Primary air: adjustable manually  
 Secondary air: adjustable manually  
 Tertiary air: fixed and preheated  
 Flue outlet top  
 Fuel: wood  
 Heating: natural convection, radiant and forced ventilation  
 Kit optional through Multifuoco System®

### TECHNICAL DATA

Room heating capacity (m In-max)	m <sup>2</sup>	235 - 405
Nominal thermal efficiency	%	78,9
Rated heat output	kW	14,1
Consumption at rated heat output	Kg/h	3,8
Maximum heat output	kW	15
Maximum consumption	Kg/h	4,6
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. m In sect.)	cm <sup>2</sup>	300
Weight	Kg	200

### ON REQUEST

- Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Full technical data available in pdf



DoP product



DoP Metal Connecting Flue Pipes

### Compatible Cover

ESSEN - GRAZ - AMBURGO - FRIBURGO - LIPSIA - COLONIA - LINZ - SALISBURGO  
 - EASY - TARANTO

### TECHNICAL DRAWING

