



MC 120/48 SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
 Fire pit: Aluker®
 Firebox: Aluker®
 Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°.
 Rise n fall door, hinged opening for cleaning
 Door profile: Enamelled steel
 Door handle: hide away and detachable
 Primary air: adjustable manually
 Secondary air: adjustable manually
 Tertiary air: fixed and preheated
 Flue outlet top
 Fuel: wood
 Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus, ducting

TECHNICAL DATA

Room heating capacity (m in-max)	m ²	235 - 405
Firebox heat output	kW	17,8
Nominal thermal efficiency	%	78,9
Rated heat output	kW	14,1
Consumption at rated heat output	Kg/h	3,8
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. m in sect.)	cm ²	300
Weight	Kg	285

On request

- Multifuoco System® ventilation kit 4 speed levels
- Multifuoco System Plus ventilation kit 4 speed levels
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Certifications

CE conformity declaration respecting norms 89/106 /CEE. Certified according to EN 13229.

*The heating capacity is calculated in rooms with a requirement between 0,000 and 0,035 kWper m², depending on their insulation.
 Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used*



The availability of models may vary from Country to Country.

Full technical data available in pdf

Compatible Cover

ESSEN - GRAZ - AMBURGO - FRIBURGO - LIPSIA - COLONIA - LINZ - SALISBURGO
 - EASY - TARANTO

TECHNICAL DRAWING

