



MC 90/44 SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox

Firebox: in Aluker®

Fire pit: in Aluker®

Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 °C. Rise n fall door

Door profile: in enamelled steel

Door handle: hide away and detachable

Primary air: adjustable manually

Secondary air: adjustable manually

Tertiary air: fixed and preheated

Flue outlet: top

Fuel: wood

Heating: natural convection, radiant and forced ventilation
kit optional through Multifuoco System®

TECHNICAL DATA

Room heating capacity (min-max)	m ³	205 - 350
Nominal thermal efficiency	%	79,3
Rated heat output	kW	12,2
Consumption at rated heat output	Kg/h	3,2
Maximum heat output	kW	14
Maximum consumption	Kg/h	4
Flue outlet	Ø cm	20
Flue up to 4,5 mt	Ø cm	25
Flue over 4,5 mt	Ø cm	20
Fresh air intake (recomm. min sect.)	cm ²	200
Weight	Kg	160

ON REQUEST

- Multifuoco System® ventilation kit 4 speed
- Combustion air kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Full technical data available in pdf

Compatible Cover

TECHNICAL DRAWING

